



Vapro VBCI-868

VBCI Wax Coating

CONFORMS TO MIL-C-83933A & MIL-C-16173E

Passed German VIA (Vapour Inhibition Ability) Test TL 8135-002

NATO STOCK NUMBER: 6850-32-076-1109

Description

Vapro VBCI-868 is a dark brown thixotropic liquid with VBCI corrosion inhibitors and oil based or solvent based carriers. The residual film, after solvent evaporation is highly resistant to salt water and salt spray, making Vapro VBCI-868 particularly useful in marine, industrial, and off-shore rust proofing applications. Vapro VBCI-868 provides optimal corrosion protection up to 24 months, for ferrous and non-ferrous metal exposed to outdoor environments.

Advantages

- Dry to touch film properties allow protected metal surfaces to be easily handled.
- Little surface preparation, as Vapro VBCI-868 will adhere to the pre-rusted surfaces.
- A thixotropic liquid, and self-healing. Thus, resistant to sag, run-off, and flow.
- Excellent U.V. resistant, providing optimal outdoor protection without cracking or chipping of protective films after prolonged exposures to sunlight.
- Universal protection for ferrous and non-ferrous metals and alloys.
- The non-conductive film with high resistivity and insulating properties effectively prevents galvanic corrosion between dissimilar metals.
- Have moisture-displacing characteristics.
- Thermally stable coatings over a broad range of temperature (30°C - 95°C).



- Applicable to the following specifications:
 - MIL-C-0083933A(MR)
 - MIL-C-16173E GRADE 4
 - FORD M7C16A
 - P.O.D. V5C65
- Vapro VBCI-868 provides high levels of corrosion resistance, up to 24 months outdoor protection in corrosive atmospheres.
- Moisture displacing and penetrating film characteristics.
- Universal protection for ferrous and non-ferrous metals and alloys.
- Easy removal by petroleum solvents.



A member of



Typical Applications

MAINTENANCE

- Protection of structural plant and equipment.
- Mothballing refineries, power plants, and chemical plants
- External surfaces of large machines, pipes, pumps, heat exchangers, etc. during standby, field storage, or operation.

PACKAGING AND SHIPPING

- Covered or uncovered packages shipped overseas and/or during extended on-site storage.

CONSTRUCTION STEELS FOR FABRICATING, STORAGE AND IN FIELD USE

- Concrete reinforcing bars, aluminum or steel sidings joints, profiles, bridges, structures, casings and steel roofs.

MARINE AND OFFSHORE

- External and internal surfaces of offshore platforms and equipment.
- Ballast tanks, storage, and process vessels.
- Castings, pumps, valves, and compressors, heat exchangers, boilers, turbines, and transformers.
- Wire rope, cable, wire, and chains.
- Internal and external surfaces of drill pipe, sucker rods, and other oil country tubular products.

OEM EQUIPMENT

- Internal and external surfaces of engines.
- Bearings, brake drums, engine components.
- Frames, cabs, stampings, castings and plate steel.
- Transmission, hydraulic pistons, cylinders, and equipment undercoating.

Directions for Use

- Dipping, spraying or brushing is recommended methods of applying. Film thickness of 2 mils to 5 mils.
- For maximum protection use Vapro VBCI-868 in concentrate form.
- For short term protection Vapro VBCI-868 can be diluted 1:1 with mineral spirits.
- Vapro VBCI-868 can be applied over pre-rusted or oily surfaces.
- Application does not require heating of inhibitor solution or increased temperatures for drying.

Specifications

Appearance

Dark brown thixotropic liquid

Film Type

Dry waxy film

Carrier

Mineral spirits/Napthenic oil

Flash Point

41°C

Specific Gravity

0.85 at 25°C

Available Packaging

20 Litres & 200 Litres drum

Magna

Magna International Pte Ltd

10H, Enterprise Road,
Singapore 629834.

Tel (65) 6786-2616

Fax (65) 6785-1497

Email info@magnachem.com.sg
info@vapprovci.com

Web <http://www.vapprovci.com>

Headquarters



Singapore

Regional Offices



Australia



Canada

Follow us on social media for regular updates and news.



<https://www.facebook.com/vapprovci/>

<https://www.facebook.com/MagnaInternationalPteLtd/>

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.



Copyright 2018. Magna International Pte Ltd.

Magna, Vapro VCI and Vapro VBCI are registered trademarks of Magna International Pte Ltd.