



ECO FRIENDLY
SUSTAINABLE
BIODEGRADABLE



VBCI Series- A class of environmentally friendly corrosion inhibitors for a cleaner, greener, better tomorrow.

Vapro VBCI-869 VBCI Grease

CONFORMS TO MIL C-83933A

Passed German VIA (Vapour Inhibition Ability) Test TL 8135-002

NATO STOCK NUMBER: 9150-32-076-1117

Description

VAPPRO VBCI-869 is a mixture of vapour corrosion inhibitors, and oil-based carriers. It is formulated to provide superior protection over conventional rust inhibiting oils/coating.

VAPPRO VBCI-869 concentrate is a grease-like material that is diluted with oil to provide self-healing and lubricating coating. VAPPRO VBCI-869 can also be added to lubricating oils to improve corrosion resistance.

Advantages

- Tacky film provides good lubrication to moving or sliding parts.
- Universal protection for ferrous and non ferrous metals and alloys.
- Thixotropic and self-healing, thus resistant to sag, run-off and flow.
- The non-corrosive film with high resistivity and insulating properties effectively prevents galvanic corrosion between dissimilar metals.
- VAPPRO VBCI-869 provides high levels of corrosion resistance, up to 24 months outdoor protection in corrosive atmosphere.
- Has moisture displacing and penetrating characteristics.
- Little surface preparation needed, as VAPPRO VBCI-869 will adhere to pre-rusted areas. Excellent U.V. resistance, providing optimal outdoor performance without cracking or chipping of protective film after prolonged exposure to sunlight.



- The product is easily removable with mineral spirits or aliphatic solvents.

Directions for Use

- When diluted with mineral oil VAPPRO VBCI-869 may be applied by oilers or electrostatic sprayers, as well as by other spray methods.
- Dipping, spraying or brushing is recommended methods of applying.
- Film thickness of 0.5 to 2 mils is recommended for indoor or sheltered protection.
- For use as an additive to R.P. oils, stamping, or drawing lubricants, dilute up to 1:10 by volume. VAPPRO VBCI-869 can be applied over pre-rusted or oil surfaces. Application does not require heating of inhibitor solution or increased temperatures for drying.



A member of



Typical Applications

Maintenance

- Mothballing refineries, power plants and chemical plants.
- Protection of structures and equipment.
- External surfaces of large machines, pipes, pumps, heat exchangers, etc. during standby, field storage or operation.

Construction Steels For Fabricating, Storage, And In Field Use

- Joints, profiles, casings.
- Steel ropes and aluminum or steel sidings.
- Bridges, structures and concrete reinforcing bars.

Metalworking And Manufacturing

- Protects any metal part, component or assembly between processing or machining steps.
- Excellent for protection of finely machined, honed, or polished surfaces where tight tolerances are important.

Marine And Utilities

- Castings, pumps, valves, and compressors.
- Internal and external surfaces of engines.
- Transmissions, hydraulic pistons, and cylinders.
- Equipment undercoating.
- Bearings, brake drums, engine components.
- Ballast tanks, storage, and process vessels.
- Wire rope, cable, wire, and chains.
- Internal and external surfaces of drill pipe, sucker rods, and other oil country tubular products.
- Frames, cabs, stampings, castings, and plate steel.

Additives To Slushing Oils Or Lubricants

- Superior gear, stamping or drawing lubricant.
- May be added to rolling oils for aluminum, cold rolled or hot rolled steels, and galvanized steel for corrosion protection.

Specifications

Appearance
Red Grease

Film Thickness, mils
2-4

Weight per gallon,lbs
8.1 lbs/gallon
0.97 kg/liter

Melting Point(Dropping Point)
207°C

Specific Gravity
0.9 ± 0.025

Flash Point(min),
205°C

Drying Time
Remains Tacky

Available Packaging

18 kg & 180kg drum

Magna

Magna International Pte Ltd

10H, Enterprise Road,
Singapore 629834.

Tel (65) 6786-2616

Fax (65) 6785-1497

Email info@magnachem.com.sg
info@vapprovci.com

Web http://www.vapprovci.com

Headquarters



Singapore

Regional Offices



Australia



Canada

Follow us on social media for regular updates and news.



<https://www.facebook.com/vapprovci/>

<https://www.facebook.com/MagnaInternationalPteLtd/>

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.



Copyright 2018. Magna International Pte Ltd.

Magna, Vapro VCI and Vapro VBCI are registered trademarks of Magna International Pte Ltd.